



# SP-800

## Vital Signs Monitor



- **NEW ON INFLATION** Non-invasive Blood pressure
- **NEW ON INFLATION** Faster and more comfortable readings
- **NEW** Integrated Power Supply
- Bi Directional Non-invasive Blood Pressure
- 'Artefact rejection' SP 800 will complete reading in the same cycle on deflation in the presence of movement
- Designed, developed & manufactured in the UK
- Simple to use, on-screen instructions
- NIBP for adult/neonate, pulse rate, SPO2 and temperature
- Alarms and printing function
- Manual mode and multiple automatic settings
- Built-in printer option
- Stores 1000 patient records
- Extremely light and portable (max 1.4Kg)
- Mains or battery operated for mobile monitoring with quick battery charging. 350 readings on one battery charge
- Two-year guarantee



## TECHNICAL SPECIFICATIONS

<b>Name and model number</b>	Vital Signs Monitor, SP-800
<b>Power source</b>	Mains: AC100-240V, AC ( $\pm 10\%$ ), 50-60Hz, ( $\pm 3\text{Hz}$ ), 40VA max. 350 measurements for NIBP. Use cables that are supplied with the SP800.
<b>Display</b>	LCD display: SYS, DIA, Mean, Pulse rate, SPO2, Temp with 8 indicators
<b>NIBP</b>	Oscillometric method
<b>Measuring range</b>	Adult mode: 40mmHg – 270mmHg Neonate mode: 20mmHg – 130mmHg
<b>Measurement Time</b>	A 120/80 measurement is < 25secs (typically)
<b>Auto mode interval setting</b>	3,4,5,10,15,20,30,60 or 90minutes (1minute interval programmable from 1min to 90 min.) / STAT for continues 10 minutes
<b>Blood pressure accuracy</b>	Meets or exceeds SP10-1992 AAMI standards for non-invasive blood pressure accuracy and the International protocol standards.
<b>Initial cuff inflation</b>	Adult: 180mmHg. Typically maximum pressure over systolic $\leq 20\text{mmHg}$ Neonate: 120mmHg / Programmable
<b>Pulse rate</b>	40-200bpm, accuracy 5%
<b>Alarm setting range</b>	Adult: SYS 50-250mmHg, DIA 40-170mmHg, Pulse: 30-200bpm Neonate: SYS 30-140mmHg, DIA 20-110mmHg, Pulse: 30-200bpm
<b>SPO2 (Optional)</b>	
<b>Measurement range</b>	40-99%
<b>Accuracy</b>	SPO2: 70-99%, $\pm 2\%$ (Adult), $\pm 3\%$ (Neonate), <70%: unspecified Pulse rate: $\pm 3\%$ (overrides NIBP calculated Pulse when active)
<b>Resolution</b>	1% SPO2
<b>Alarm setting range</b>	40-99%
<b>TEMP (Optional)</b>	
<b>Measurement range</b>	28.9°C – 42.2°C (84.0°F – 108.0°F)
<b>Accuracy (including probe)</b>	Meets ASTM E112-86 "Standard Specification for Electronic Thermometer for Intermittent Determination of Patient Temperature".
<b>Resolution</b>	$\pm 0.1^\circ\text{C}$ ( $\pm 0.2^\circ\text{F}$ )
<b>Average time constant</b>	Oral: 4 seconds typical / Axillary: 10 seconds typical / Rectal: 15 seconds typical
<b>Alarm setting range</b>	Range: 28.9°C – 42.2°C (84.0°F – 108.0°F)
<b>Printer</b>	24 column thermal printer
<b>PC interface</b>	RS-232 can be connected to a PC
<b>Operating environment</b>	+10°C to +40°C (+50°F to +104°F), less than 85% RH
<b>Storage environment</b>	-20°C to +50°C (-4°F to +122°F), less than 85% RH
<b>Dimensions</b>	166(D) x 216(W) x 194(H) / mm
<b>Weight</b>	Approx 1.4Kg with all options
<b>Safety</b>	Designed and manufactured in accordance with IEC60601-1 / UL60601-1
<b>Certification No.</b>	Device under test - launch date 2017
<b>Country of Origin</b>	United Kingdom
These specifications are subject to change without prior notice for purpose of improvement.	

## ACCESSORIES

- Adult cuff
- Large adult cuff
- Child cuff
- Hose Assembly
- AC power adapter
- Printing roll paper
- User manual
- Neonate cuff A,B,C (optional)
- Neonate cuff hose connector (optional)
- SPO2 sensor probe (optional)
- Temperature sensor probe (optional)
- Mobile stand with basket (optional)



**G-CARE**  
Medical

Marturion House  
Knockmore Hill Business Park  
9 Ferguson Drive, Lisburn  
BT28 2EX, United Kingdom

Tel: +44 (0)28 9266 0118  
Fax: +44 (0)28 9266 9943  
Email: sales@gcaremedical.com